

# Hydraulic Torque Pumps

HE-Series  
800 Bar

- Working pressure 800 bar maximum
- 40-800 bar stepless pressure adjustment available
- Multipoint connection for more torque wrenches
- Double and three stage high performance pump units
- Calibrated, Clas 1, 1000 bar, Ø 100mm precision gauge
- Designed for high performance and continuous operations
- Oil filter, oil cooler and flat stable oil tank by FE series
- Oil level indicator - thermometer and protecting frame
- German made with CE marking, after sales service in Turkey



HE-055-2



HE-025-3

Model No	HE-025-3-230	HE-055-2-230
Operating Voltage	110 / 115 / 230 Voltage	110 / 115 / 230 Voltage
Electric Motor Power	0,25 kW	0,37 kW
Oil Displacement	3 - Stages	2 - Stages
Flow Rate	3,2 - 0,9 - 0,4 L/min.	5,0 - 0,7 L/min.
Oil Capacity	3 Litre	5 Litre
Carrying Handle	Available	Available
Cooling System	Non-existence	Non-existence
Weight	23 Kg	29 Kg
Sizes (U-G-Y)	36 x 30 x 44 cm	45 x 34 x 52 cm
Recommended Oils	Mobil DTE24 - Tellius 32 - Energol HLP-HM32	

## Surkon Makina Sanayi Ticaret Limited Şirketi

İvedik Org. San. Bölgesi - Özpetek Sanayi Sitesi 1390 Sokak.- No: 12 – TR-06378 – Yenimahalle / ANKARA Tel: (0 312) 386 14 64 / Faks: (0 312) 386 14 88  
e-mail : eposta@surkon.com [www.surkonmakina.com](http://www.surkonmakina.com)

**SURKON**<sup>®</sup>  
INTERNATIONAL