





DATA SHEET BT-2015

2000 bar Hand Pump

This hand pump can be used with all BOLTIGHT 2000 bar tooling and equipment. The pump has both high and low pressure pistons and is supplied complete with, a 110 mm diameter pressure gauge, pressure release valve, internal pressure safety relief valve (set at 2000 bar), a 2.4 litre oil reservoir and a self sealing quick connect coupling (Type C) fitted with a red plastic dust cap.

Hand pumps should only be used with one or two tensioning tools. When simultaneous operation of several tools is being considered BOLTIGHT recommends the use of an air driven pump.





Specification:

Part No
Dimensions
Weight
Oil Reservoir
Finish
Pressure Gauge
Maximum Pressure
Internal Pressure Relief Valve set at
Oil Delivery Low Pressure Piston
Oil Delivery High Pressure Piston
Handle Effort @ 2000 bar

BT-2015
620 mm long x 130 mm wide x 170 mm high
11 kgs
2.4 litre ISO 10 hydraulic oil
Aluminium Silver and Black
0 - 3000 bar 0 - 45,000 psi
2400 bar
2000 bar
20 cc per stroke
0.7 cc per stroke
420 Newtons

ww.boltight.com Copyright Boltight Ltd May 2006

ADRAOFIC ROFI LENZIONING

DATA SHEET BT-2014

2000 bar Hand Pump Range

These hand pumps can be used with all BOLTIGHT 2000 bar tooling and equipment. The pumps have both high and low pressure pistons and are supplied complete with, a damped (liquid filled) pressure gauge, pressure release valve, internal pressure safety relief valve, an oil reservoir and a self sealing quick connect coupling (Type C - see DS 26).

If 63 mm or 110 mm diameter pressure gauges are too small, larger external pressure gauges (including boxed test gauges) are available. These are fitted with quick connectors and a gauge adaptor and are connected directly to the outlet quick connect coupling of the pump. Contact BOLTIGHT for details.





Part No BT-2014C

2.4 litre oil reservoir63 mm diameter pressure gauge



Part No BT-2014D

2.4 litre oil reservoir110 mm diameter pressure gauge