

- Real 720 bar operating pressure, 2880 bar burst pressure
- Made from polyflex material, slim and flexible design
- 2 spiral layers of high tensile steel wire covered by plastic
- High strength, suitable for use in hydraulic oil
- Twin hose available in almost all RAL colours
- Low volumetric expansion of 3,1 ml/m
- Made in Germany, brand Parker with CE marking



Model No								
	Working Pressure		Burst Pressure		Inner D.-	Outer D.	Bend Radius	Weight
**	bar	psi	bar	psi	mm	mm	mm	kg/m
2340N-04V10	720	10.440	2.880	41.760	6,4	12,5	70	0,25



Working Pressure	720 bar
Burst Pressure	2.880 bar
Safety Factor	1:4
Inner Diameter	6,4 mm ±0,1mm (¼")
Outer Diameter	12,5 mm ±0,1mm
Bend Radius	70 mm
Inner Core	Polyamid PA12
Pressure Reinforcement	2 spiral layers 2 open spiral layers of high tensile steel wire
Outer Core	TPU
Change in Length	± 2 %
Volumetric Expansion	10,0%
Impulse Strenght	> 200.000 impulse cycles (acc. to DIN EN ISO 6803)
Operating Temperature	-40 C° + 100 C°